## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	EHEIM aquaclassLED
--------------------------------	--------------------

Supplier's address: Service, Plochinger Straße 54, 73779 Deizisau, DE

Model identifier: 7239740 EHEIM aquaclassLED 66

Tν	pe	of	light	source	:
٠,	<b>P</b> C	٠.		504.00	••

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	EHEIM power supply 24 V DC		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers
Product parameters			

## Product parameters

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
	nption in on- 00 h), rounded st integer	12	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 083 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	7 900
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	11,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	92
Outer dimen-	Height	35	Spectral power dis-	See image
sions without	Width	576	tribution in the	in last page
separate con- trol gear, light-	Depth	53	range 250 nm to 800 nm, at full-load	

ing control parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,303
		nates (x and y)	0,287
Parameters for LED and OLED light sources:			
R9 colour rendering index value 91		Survival factor	1,00
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

## **Spectral Power Distribution**

